

PEDESTRIAN PUSHBUTTON KIT - GEL 250 - MODIFIED



- Modified adaptor
- Bolt on mounting
- Neoprene gasket
- Ready to install
- Palm button: polished aluminum
- One piece construction
- Powder coated
- Screen painted hi-lites
- Black on white
- (other colour combinations upon request)
- Palm button and pushbutton are secured with medium strength adhesive
- Internal working parts coated with multi-purposc lubricant with teflon
- Temperature range: -54 to 176 degrees Celsius continuous
- Lubricant: waterproof
- Standard stainless mounting hardware
- - 4 only 8/32 x 1 3/4 hex head bolts
- 1 per box
- Shipping box weight - 1 lb 4 oz
- 8 boxes per carton
- Shipping carton weight - 5 lbs 9 oz

COMMERCIAL GRADE PUSHBUTTON

- Double-break switch
- Epoxy seal to protect interval contacts and terminals
- Pushbutton: CSA approved
- Dust-tight
- Waterproof: submersible to 3 feet water pressure
- Mechanical life: 1,000,000 cycles
- Normally open
- Case: aluminum anodized clear
- Soldered closed loop lead: 12' (3.68 m)
- Solder contact coated: silicon conformal coating
- Wire: 1417 RW90 purple
- Wire: CSA approved



Greenlite Traffic

P.O. Box 64551
Coquitlam, B.C. V3J 7V7
Website: <http://www.GreenliteTraffic.com>

Phone: (604) 936-1961
Fax: (604) 936-1922
Toll Free: 1-888-936-1961
Email: info@GreenliteTraffic.com